

Product data sheet

Specifications



APC Netshelter Rack Automatic Transfer Switch, 2U, 32A, 230V, 2 IEC 309 IN, 16 C13, 2 C19 OUT, 50/60 Hz

AP4424A

Overview

Lead time Usually in Stock

Main

Main Input Voltage	230 V AC 1 phase
Product or Component Type	Automatic transfer switch
Main Output Voltage	230 V AC 1 phase
Input Connection Type	IEC 60320 IEC 60309 32 A 2P+E IEC 60320
Number of rack unit	2U
Cable length	8 ft (2.4 m)
Number of cables	2
Provided Equipment	Mounting Hardware Rack Mounting brackets

Physical

Color	Black
Height	3.5 in (8.8 cm)
Width	17.008 in (43.2 cm)
Depth	9.3 in (23.6 cm)
Net Weight	15.30 lb(US) (6.94 kg)
Mounting Location	Front Rear
Mounting preference	No preference
Mounting Mode	Rack-mounted
Mounting position	Horizontal

Input

Input Frequency	50/60 Hz
Acceptable Input Voltage	207...253 V
Load Capacity	7400 VA

Output

Maximum Total Current Draw per Phase	32 A
Number of power socket outlets	18

Protection Type	Circuit breaker
-----------------	-----------------

Conformance

Product Certifications	EN 55022 class A FCC part 15 class A
------------------------	-----------------------------------------

Standards	EN 55022 Class A FCC Part 15 class A
-----------	-----------------------------------------

Environmental

Ambient Air Temperature for Operation	23...113 °F (-5...45 °C)
---------------------------------------	--------------------------

Relative Humidity	5...95 %
-------------------	----------

Operating altitude	0...10000 ft
--------------------	--------------

Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
-------------------------------------	----------------------------

Storage Relative Humidity	5...95 %
---------------------------	----------

Ordering and shipping details

GTIN	731304432456
------	--------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	8.3 in (21 cm)
------------------	----------------

Package 1 Width	23.0 in (58.4 cm)
-----------------	-------------------

Package 1 Length	14.02 in (35.6 cm)
------------------	--------------------

Package 1 Weight	20.79 lb(US) (9.43 kg)
------------------	------------------------

Unit Type of Package 2	PAM
------------------------	-----

Number of Units in Package 2	20
------------------------------	----

Package 2 Height	47.2 in (120 cm)
------------------	------------------

Package 2 Width	39.4 in (100 cm)
-----------------	------------------

Package 2 Length	47.2 in (120 cm)
------------------	------------------

Package 2 Weight	443.6 lb(US) (201.2 kg)
------------------	-------------------------

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)



Transparency RoHS/REACH

Well-being performance

Toxic Heavy Metal Free

Lead Free

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant
[EU RoHS Declaration](#)

China Rohs Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Circularity Profile [End of Life Information](#)

California Proposition 65 "WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov"

Image of product / Alternate images

Alternative

